



Prodotto: MB SKT775 ASUS P5KPL-AM EPU

Codice:

Eventuali Ulteriori informazioni:

Valuable Intel G31 uATX solution with FSB overclocking 1600MHz!

- Intel® Core™2 Quad Ready
- Intel® 45nm CPU Ready
- FSB 1600(O.C.)/1333/1066/800 MHz
- Intel® G31/ICH7
- Dual channel DDR2 1066(O.C.)/800/667
- EZ Flash2 & CrashFree BIOS3
- 8 Channel High Definition Audio

Specifiche tecniche

CPU	Intel® Socket 775 Core™2 Quad/Core™2 Extreme/Core™2 Duo/Pentium® D/Pentium® 4/Celeron® E1000 Series and Celeron 400 Series Intel® Hyper-Threading Technology ready *Refer to www.asus.com for Intel CPU support list
Chipset	Intel® G31 Intel ICH7
Front Side Bus	1600*/1333/1066/800 MHz (*1600 is overclock speed)
Memory	2 x DIMM, Max. 4 GB, DDR2 1066(O.C.)/800/667 Non-ECC,Un-buffered Memory Dual Channel memory architecture *Overclock speed **Refer to www.asus.com or user manual for Memory QVL (Qualify Vendor List) ***When installing total memory of 4GB capacity or more, WindowsR 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

Expansion Slots	1 x PCIe x16 1 x PCIe x1 2 x PCI
VGA	Integrated Intel Graphics Media Accelerator (Intel® GMA 3100) Max. resolution:2048x1536X32bpp, Horizontal:127.5KHz Vertical:85Hz
Storage	Southbridge 1 xUltraDMA 100/66/33 4 xSATA 3 Gb/s ports
LAN	Realtek RTL8102EL 100/10 LAN
Audio	VIA VT1708B 8 -Channel High-Definition Audio CODEC Anti-Pop Function Jack-detect & Multi-Streaming Support S/PDIF Out connector
USB	8 USB 2.0 ports (4 ports at mid-board, 4 ports at back panel)
Overclocking Features	SFS (Stepless Frequency Selection) - FSB tuning from 200MHz up to 600MHz at 1MHz increment Overclocking Protection - ASUS C.P.R.(CPU Parameter Recall)
Special Features	ASUS MyLogo 2 ASUS EZ Flash 2 ASUS CrashFree BIOS 3 ASUS Q-Fan
Back Panel I/O Ports	1 x Parallel 1 x VGA 1 x PS/2 Keyboard 1 x PS/2 Mouse 1 x LAN(RJ45) port 4 x USB 2.0/1.1 1 x COM port 8 -Channel Audio I/O
Internal I/O Connectors	2 x USB connectors support additional 4 USB ports 1 x Floppy disk drive connector 1 x IDE connector 4 x SATA connectors 1 x internal speaker connector 1 x S/PDIF Out connector 1 x CPU/ Chassis/ Power Fan connector 1 x Front panel High Definition audio connector 1 x Chassis Intrusion connector 1 x CD audio in connector 24-pin EPS 12V Power connector 4-pin ATX 12V Power connector 1 x System Panel connector
BIOS	8 Mb Flash ROM DMI 2.0 AMI BIOS PnP WfM 2.0

	SM BIOS 2.5 ACPI 2.0
Manageability	WOL,PXE,RPL,WOR ,PME Wake Up
Accessories	User's manual 1 x UltraDMA 133/100/66 cable 1 x Floppy disk drive cable 1 x SATA cable 1 x SATA power cable I/O Shield
Support Disc	Drivers ASUS PC Probe II Anti-virus software (OEM version) ASUS Update
Form Factor	uATX Form Factor 9.6 inch x8 inch (24.4 cm x 20.3 cm)